



PMMA plattor – Perspex® klar

Kvalitet: Extruderade (XT)	Tjocklek	Längd	Bredd	Ljus-	Art.nr.
Färg: Klar 0X00	mm	mm	mm	trans. (%)	
Densitet: 1,19 g/cm ³	2,0	3050	2050	92	104747
	3,0	3050	2050	92	104754
	4,0	3050	2050	92	104763
	5,0	3050	2050	92	104770
	6,0	3050	2050	92	104779
	8,0	3050	2050	92	104784
	10,0	3050	2050	92	337807
	12,0	3050	2050	92	347561
	15,0	3050	2050	92	339736
	20,0	3050	2050	92	340293
	25,0	3050	2050	92	348125

PMMA plattor - Perspex® Antireflex

Kvalitet: Extruderad (XT)	Tjocklek	Längd	Bredd	Ljus	Art.nr.
Färg: Antireflex AR0X00	mm	mm	mm	trans. (%)	
Densitet: 1,19 g/cm ³	2,0	3050	2050	92	339518
	3,0	3050	2050	92	339521

PMMA plattor extruderade - Perspex® Opal 1x10

Kvalitet: Extruderad	Tjocklek	Längd	Bredd	Area	Art. nr.
Färg: OPAL 1X10	mm	mm	mm	m²/stk.	
Densitet: 1,19 g/cm ³	2,0	3050	2050	6,25	339506
	3,0	3050	2050	6,25	339507
	4,0	3050	2050	6,25	339508
	5,0	3050	2050	6,25	339509

PMMA plattor slagålig - Perspex® klar IM60

Kvalitet: Slagålig	Tjocklek	Längd	Bredd	Area	Art. nr.
Färg: KLAR IM60	mm	mm	mm	m²/stk.	
Densitet: 1,19 g/cm ³	2,0	3050	2050	6,25	343702
	3,0	3050	2050	6,25	343703
	4,0	3050	2050	6,25	343704
	5,0	3050	2050	6,25	348127

PMMA, plattor slagålig - Perspex® OPAL IM60

Kvalitet: Slagålig	Tjocklek	Längd	Bredd	Area	Art. nr.
Färg: OPAL IM60	mm	mm	mm	m²/stk.	
Densitet: 1,19 g/cm ³	3,0	3050	2050	6,25	348128
	4,0	3050	2050	6,25	348129
	5,0	3050	2050	6,25	348130



PMMA plattor - Perspex® KLAR 000

Kvalitet: Gjutet Färg: Klar Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	104762
	4,0	3050	2030	6,19	104765
	5,0	3050	2030	6,19	104773
	6,0	3050	2030	6,19	104783
	8,0	3050	2030	6,19	104786
	10,0	3050	2030	6,19	104788
	12,0	3050	2030	6,19	104789
	15,0	3050	2030	6,19	104792
	20,0	2030	1520	3,09	345119
	20,0	3050	2030	6,19	104794
	25,0	2030	1520	3,09	545120
	25,0	3050	2030	6,19	104795
40,0	2020	1290	2,61	340286	

PMMA plattor - Perspex® RÖKFÄRGAD Neutral

Kvalitet: Gjutet Färg: Rökfärgad Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	6,0	3050	2030	6,19	104852
	8,0	3050	2030	6,19	344772
	10,0	3050	2030	6,19	377533
15,0	3050	2030	6,19	377534	

PMMA plattor - Perspex® BLOCK klar 000

Kvalitet: Gjutet Färg: Klar Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	30,0	2000	1500	3,00	336867
	40,0	1800	1400	2,52	104797
	50,0	2020	1290	2,84	338848
60,0	2020	1290	2,84	348165	

PMMA plattor - Perspex® OPAL 1T2B

Kvalitet: Gjutet Färg: Opal 1T2B Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	60,0	2020	1290	2,84	348165

PMMA plattor - Perspex® OPAL 1T05

Kvalitet: Gjutet Färg: Opal 1T05 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art.nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	341319
	4,0	3050	2030	6,19	341320
	5,0	3050	2030	6,19	341321
	6,0	3050	2030	6,19	341322
	8,0	3050	2030	6,19	341323
	10,0	3050	2030	6,19	341324
	12,0	3050	2030	6,19	175650
	15,0	3050	2030	6,19	341325
	20,0	3050	2030	6,19	341326



PMMA plattor - Perspex® OPAL 028

Kvalitet: Gjuten Färg: OPAL 028 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2050	6,25	104905
	4,0	3050	2050	6,25	104917
	5,0	3050	2050	6,25	104922

PMMA plattor - Perspex® OPAL 069

Kvalitet: Gjuten Färg: Opal 069 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art.nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	104903
	4,0	3050	2030	6,19	348175
	5,0	3050	2030	6,19	104925
	6,0	3050	2030	6,19	104926
	8,0	3050	2030	6,19	341893
	10,0	3050	2030	6,19	104930

PMMA plattor gjutna - Perspex® INFRARED

Kvalitet: Gjuten Färg: Svart 962 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art.nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	104886
	4,0	3050	2030	6,19	175625
	10,0	3050	2030	6,19	104890
	20	3050	2030	6,19	384385



PMMA, rör – VINK® PMMA

Kvalitet: Extruderad Färg: Klar Densitet: 1,19 g/cm ³	Utvändig	Tolerans utvändig	Invändig	Tolerans invändig	Längd	Art.nr.
	Ø mm	Ø %	Ø mm	Ø %	mm	
Alla rör levereras med PE skyddsfolie.	Ø 8	+/-1,0	Ø 4	+/-1,5	2000	103428
	Ø 10	+/-1,0	Ø 7	+/-1,5	2000	103429
Leveranser från fabrik levereras med följande minimimängder: Ø 8 - Ø 20 mm: 10 stk. pr. sats Ø 22 - Ø 36 mm: 5 stk. pr. sats Ø 38 - Ø250 mm: 1 stk. pr. sats	Ø 10	+/-1,0	Ø 8	+/-1,5	2000	108704
	Ø 12	+/-1,0	Ø 8	+/-1,5	2000	103432
	Ø 13	+/-1,0	Ø 10	+/-1,5	2000	103434
	Ø 15	+/-1,0	Ø 11	+/-1,5	2000	103437
	Ø 20	+/-1,0	Ø 14	+/-1,5	2000	103440
	Ø 20	+/-1,0	Ø 16	+/-1,5	2000	103441
	Ø 20	+/-1,0	Ø 16	+/-1,5	2200	380397
	Ø 25	+/-1,0	Ø 19	+/-1,5	2000	103443
	Ø 25	+/-1,0	Ø 21	+/-1,5	2000	103442
	Ø 30	+/-1,0	Ø 20	+/-1,5	2000	103446
	Ø 30	+/-1,0	Ø 24	+/-1,5	2000	103445
	Ø 30	+/-1,0	Ø 26	+/-1,5	2000	103444
	Ø 40	+/-1,0	Ø 32	+/-1,5	2000	107130
	Ø 40	+/-1,0	Ø 34	+/-1,5	2000	103449
	Ø 40	+/-1,0	Ø 36	+/-1,5	2000	103448
Ø 50	+/-1,0	Ø 42	+/-1,5	2050	331813	
Ø 50	+/-1,0	Ø 44	+/-1,5	2050	103453	
Ø 60	+/-1,0	Ø 52	+/-1,5	2050	103457	
Ø 60	+/-1,0	Ø 54	+/-1,5	2050	103456	
Ø 70	+/-1,0	Ø 64	+/-1,5	2050	103459	
Ø 80	+/-1,0	Ø 72	+/-1,5	2050	103465	
Ø 80	+/-1,0	Ø 72	+/-1,5	2050	103464	
Ø 90	+/-1,0	Ø 84	+/-1,5	2050	103467	
Ø100	+/-1,0	Ø 90	+/-1,5	2050	103472	
Ø100	+/-1,0	Ø 94	+/-1,5	2050	103470	
Ø110	+/-1,0	Ø100	+/-1,5	2050	103474	
Ø110	+/-1,0	Ø104	+/-1,5	2050	103473	
Ø120	+/-1,0	Ø114	+/-1,5	2050	103475	
Ø130	+/-1,0	Ø124	+/-1,5	2050	103480	
Ø134	+/-1,0	Ø128	+/-1,5	2050	103483	
Ø150	+/-1,0	Ø144	+/-1,5	2050	103484	
Ø180	+/-2,0	Ø172	+/-2,5	2050	103487	
Ø180	+/-2,0	Ø174	+/-2,5	2050	378882	
Ø200	+/-2,0	Ø190	+/-2,5	2050	103492	
Ø200	+/-2,0	Ø194	+/-2,5	2050	103489	
Ø250	+/-2,0	Ø244	+/-2,5	2050	103493	
Ø300	+/-2,0	Ø244	+/-2,5	2050	103497	



PMMA rundstänger – VINK® PMMA

Kvalitet: Gjuten, blank

Färg: Klar

Densitet: 1,20 g/cm³

Tolerans på längd: +2,0/0 mm

Utvändig	Tolerans utvändigt	Längd	Vikt	Art.nr.
Ø mm	Ø mm	mm	kg/m	
Ø 2	+/-0,1	1000	0,01	368589
Ø 5	+/-0,1	1000	0,03	106012
Ø 10	+/-0,1	1000	0,10	107181
Ø 12	+/-0,1	1000	0,14	107182
Ø 15	+/-0,1	1000	0,23	107183
Ø 18	+/-0,1	1000	0,32	107185
Ø 20	+/-0,1	2000	0,80	106021
Ø 25	+/-0,1	1000	0,62	107188
Ø 30	+/-0,3	1000	0,90	107189
Ø 30	+/-0,3	2000	1,80	106023
Ø 40	+/-0,3	1000	1,53	107191
Ø 50	+/-0,3	1000	2,33	107192
Ø 60	+/-0,3	1000	3,59	107193
Ø 70	+/-0,5	1000	4,87	106029
Ø100	+/-0,5	1000	9,50	106032
Ø110	+/-0,5	1000	11,62	107197
Ø120	+/-0,5	1000	13,60	117580
Ø150	+/-0,5	1000	25,56	133602

PMMA, fyrkantör – VINK® PMMA

Kvalitet: Gjuten

Färg: Klar

Densitet: 1,19 g/cm³

Utvändig	Tolerans utvändigt	Invändigt	Tolerans invändigt	Längd	Art.nr.
mm	%	mm	%	mm	
10,0		10,0		2000	125898



PMMA plattor - VIKUglass klar

Kvalitet: Extruderad Färg: Klar Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	1,5	3050	2050	6,25	368311
	2,0	3050	2050	6,25	368312
	3,0	3050	2050	6,25	368316
	4,0	3050	2050	6,25	206065
	5,0	3050	2050	6,25	368318
	6,0	3050	2050	6,25	368319
	8,0	3050	2050	6,25	368320
	10,0	3050	2050	6,25	368321
	12,0	3050	2050	6,25	368322
15,0	3050	2050	6,25	394958	

PMMA plattor - VIKUglass opal

Kvalitet: Extruderad Färg: Opal R7064 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	2,0	3050	2050	6,25	386554
	3,0	3050	2050	6,25	323036
	4,0	3050	2050	6,25	386555
5,0	3050	2050	6,25	386556	

PMMA plattor - VIKUglass HI, slagålig klar

Kvalitet: Extruderad Färg: Klar HI Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	2,0	3050	2050	6,25	386562
	3,0	3050	2050	6,25	386559
	4,0	3050	2050	6,25	386561
5,0	3050	2050	6,25	386563	

PMMA plattor - VIKUglass HI, slagålig opal

Kvalitet: Extruderad Färg: Opal HI R7564 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2050	6,25	386569
4,0	3050	2050	6,25	386570	

PMMA plattor - VIKUglass HI, antireflex klar

Kvalitet: Extruderad Färg: Antireflex klar R7069 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	2,0	2050	1250	2,56	386567
3,0	2050	1250	2,56	386568	

PMMA plattor - VIKUglass färg

Kvalitet: Extruderad Färg: Svart R7058/Vit R7067 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2050	6,25	388697
	5,0	3050	2050	6,25	388698
	3,0	3050	2050	6,25	388699
5,0	3050	2050	6,25	388700	



PMMA plattor - VIKUGREEN 100% återvunnen akryl

Kvalitet: Gjuten Färg: Klar Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	383994
	4,0	3050	2030	6,19	383995
	5,0	3050	2030	6,19	383996
	6,0	3050	2030	6,19	334202
	8,0	3020	2020	6,10	386479
	10,0	3050	2030	6,19	383997
	12,0	3020	2020	6,10	389130
	15,0	3020	2020	6,10	389131
	18,0	3000	2000	6,00	389132
	20,0	3050	2030	6,19	383998
25,0	3000	2000	6,00	389133	

PMMA plattor - VIKUGREEN 100 % återvunnen akryl

Kvalitet: Gjuten Färg: Opal 72006 Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	389065
	5,0	3050	2030	6,19	389066
10,0	3050	2020	6,16	389069	

PMMA plattor - VIKUGREEN 100% återvunnen akryl

Kvalitet: Gjuten Färg: Vit Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
	3,0	3050	2030	6,19	390848
	3,0	3050	2030	6,19	388466
	5,0	3050	2030	6,19	390849
	5,0	3050	2030	6,19	390125
	8,0	3020	2020	6,10	390850
	8,0	3020	2020	6,10	390853
	10,0	3020	2020	6,10	390851

PMMA plattor - VIKUGREEN 100 % återvunnen akryl

Kvalitet: Gjuten Färg: Svart Densitet: 1,19 g/cm ³	Tjocklek	Längd	Bredd	Area	Art. nr.
	mm	mm	mm	m ² /stk.	
3,0	3050	2030	6,19	390854	