





## POM C, plattor – Ertacetal® C-LGM\*, Natur - QEPP

POM C, plattor Ertacetal® C Kvalitet: Extruderad Färg: Natur Densitet: 1,41 g/cm <sup>3</sup>		Tjocklek	Tolerans tjocklek	Längd	Bredd	Teoretisk vikt	Art. nr.
		mm	mm	mm	mm	kg/stk	
De angivna vikterna är genom- snittliga produktionsvikter.		1,0	+/-0,10	2000	1000	2,90	108141
		2,0		2000	1000	5,82	108157
		3,0	+/-0,15	2000	1000	8,72	108162
		4,0	+/-0,20	2000	1000	11,60	108170
		5,0	+/-0,25	2000	1000	14,50	108174
		6,0	+/-0,25	2000	1000	17,45	108177
		8,0	+0,2/+0,9	2000	1000	24,80	326962*
		10,0	+0,2/+0,9	2000	1000	30,70	326940*
		12,0	+0,2/+1,5	2000	1000	37,50	326941*
		12,0	+0,2/+1,5	2000	1000	37,50	324251
		16,0	+0,2/+0,9	2000	1000	49,10	326943*
		20,0	+0,3/+1,5	2000	1000	60,70	326944*
		25,0	+0,5/+1,5	2000	1000	75,20	326945*
		25,0	+0,5/+1,5	3000	610	69,45	108195
		30,0	+0,5/+2,5	2000	1000	91,50	326946*
		40,0	+0,5/+2,5	2000	1000	120,60	326532*
		50,0	+0,5/+3,5	2000	1000	149,60	326949*
		60,0	+0,5/+3,5	3000	610	166,35	327802*
		70,0	+0,5/+3,5	3000	610	193,20	326961*
		80,0	+0,5/+5,0	3000	610	222,00	327143*
90,0	+0,5/+5,0	3000	610	193,20	366022*		
100,0	+0,5/+5,0	1000	610	91,90	326952*		

## POM C, plattor – Ertacetal® C-LGM\*, Svart - QEPP

POM C, plattor Kvalitet: Extruderad Färg: svart Densitet: 1,41 g/cm <sup>3</sup>		Tjocklek	Tolerans tjocklek	Längd	Bredd	Teoretisk vikt	Art. nr.
		mm	mm	mm	mm	kg/stk	
De angivna vikterna är genom- snittliga produktionsvikter.		5,0	+0,2/+0,9	2000	1000	14,67	385049
		8,0	+0,2/+0,9	3000	610	22,95	116440
		10,0	+0,2/+0,9	2000	1000	30,70	326953*
		12,0	+0,2/+1,5	3000	610	34,65	124944
		15,0	+0,3/+1,5	2000	1000	46,20	322269
		15,0	+0,3/+1,5	3000	610	42,60	108311
		20,0	+0,2/+0,9	2000	1000	60,70	326954*
		25,0	+0,3/+1,5	2000	1000	75,90	322101
		25,0	+0,3/+1,5	3000	610	69,45	114910
		30,0	+0,5/+2,5	2000	1000	91,50	326956*
		30,0	+0,5/+2,5	3000	610	84,60	108334
		40,0	+0,5/+2,5	2000	1000	120,60	326963*
		50,0	+0,5/+2,5	1000	610	46,05	326957
		50,0	+0,5/+2,5	2000	1000	149,60	322102
		60,0	+0,5/+3,5	1000	610	55,45	326958
		60,0	+0,5/+3,5	3000	610	166,35	366019*
		70,0	+0,5/+3,5	3000	610	193,20	352017
		80,0	+0,5/+5,0	3000	610	222,00	330867
		100,0	+0,5/+5,0	1000	610	91,90	326959
		100,0	+0,5/+5,0	3000	610	275,70	119181

\*) LGM = Livsmedelsgodkänt material



## POM C, rundstänger – Ertacetal® C LGM\*, Natur - QEPP

POM C, rundstänger Kvalitet: Extruderat Färg: Natur Densitet: 1,41 g/cm <sup>3</sup>  Tolerans på längden: 0/+3 % Tolerans med enligt DIN 15860 De angivna vikterna är genomsnittliga produktionsvikter.	Utvändig	Tolerans utväändigt	Längd	Teoretisk vikt	Art. nr.
	Ø mm	Ø mm	mm	kg/stk	
	Ø 3	+0,1/+0,3	3000	0,04	366024
	Ø 4	+0,1/+0,3	3000	0,06	108728
	Ø 5	+0,1/+0,4	3000	0,10	108732
	Ø 6	+0,1/+0,4	3000	0,14	108740
	Ø 8	+0,1/+0,5	3000	0,24	108744
	Ø 10	+0,1/+0,5	3000	0,36	108749
	Ø 12	+0,2/+0,7	3000	0,53	108756
	Ø 15	+0,2/+0,7	3000	0,81	108761
	Ø 16	+0,2/+0,7	3000	0,92	108767
	Ø 18	+0,2/+0,7	3000	1,16	108770
	Ø 20	+0,2/+0,7	3000	1,42	327041*
	Ø 22	+0,2/+0,9	3000	1,73	108778
	Ø 25	+0,2/+0,9	3000	2,22	327042*
	Ø 28	+0,2/+0,9	3000	2,78	108786
	Ø 30	+0,2/+0,9	3000	3,18	327043*
	Ø 32	+0,2/+1,1	3000	3,63	108793
	Ø 36	+0,2/+1,1	3000	4,56	327044*
	Ø 40	+0,2/+1,1	3000	5,61	326628*
	Ø 45	+0,3/+1,3	3000	7,11	327045*
	Ø 50	+0,3/+1,3	3000	8,76	327046*
	Ø 56	+0,3/+1,3	3000	10,95	108579
	Ø 60	+0,3/+1,6	3000	12,60	327023*
	Ø 65	+0,3/+1,6	3000	14,76	327025*
	Ø 70	+0,3/+1,6	3000	17,07	327027*
	Ø 75	+0,4/+2,0	3000	19,71	108606
	Ø 80	+0,4/+2,0	3000	22,38	327029*
	Ø 85	+0,5/+2,2	3000	25,29	108637
	Ø 90	+0,5/+2,2	3000	28,29	327030*
	Ø 100	+0,6/+2,5	3000	34,95	327031*
	Ø 110	+0,7/+3,0	3000	42,45	326888*
	Ø 120	+0,8/+3,5	3000	50,70	327032*
	Ø 130	+0,9/+3,8	3000	59,40	327033*
	Ø 140	+0,9/+3,8	1000	22,90	333825*
	Ø 150	+1,0/+4,2	1000	26,35	327035*
	Ø 160	+1,1/+4,5	1000	30,00	327062*
	Ø 170		1000	33,90	108677
	Ø 180	+1,2/+5,0	1000	37,90	327037*
	Ø 200	+1,3/+5,5	1000	46,80	327038*
	Ø 230	+1,5/+6,2	1000	61,45	118418
	Ø 250	+1,5/+6,2	1000	72,85	327040*
	Ø 300	+1,7/+7,0	1000	104,70	124973
	Ø 320	+1,8/+7,4	1000	119,00	128806

\*) LGM - Livsmedelsgodkänt Material



## POM C, rundstänger – Ertacetal® C LGM\*

POM C, rundstänger Ertacetal® C Kvalitet: Extruderat Färg: Svart Densitet: 1,41 g/cm <sup>3</sup>	Utvändig	Tolerans utvändigt	Längd	Teoretisk vikt	Art. nr.
	Ø mm	Ø mm	mm	kg/stk	
Tolerans på längden: 0/+3 % Tolerans med enligt DIN 15860 De angivna vikterna är genomsnittliga produktionsvikter.	Ø 5	+0,1/+0,4	3000	0,10	122799
	Ø 6	+0,1/+0,4	3000	0,14	108857
	Ø 8	+0,1/+0,5	3000	0,24	108859
	Ø 10	+0,1/+0,5	3000	0,36	108886
	Ø 12	+0,2/+0,7	3000	0,53	108911
	Ø 16	+0,2/+0,7	3000	0,92	108916*
	Ø 18	+0,2/+0,7	3000	1,16	108921
	Ø 20	+0,2/+0,7	3000	1,42	327051*
	Ø 22	+0,2/+0,9	3000	1,77	112848
	Ø 25	+0,2/+0,9	3000	2,22	327052*
	Ø 28	+0,2/+0,9	3000	2,78	108934
	Ø 30	+0,2/+0,9	3000	3,18	327053*
	Ø 32	+0,2/+0,9	3000	3,63	108940
	Ø 36	+0,2/+0,9	3000	4,56	327056*
	Ø 40	+0,2/+0,9	3000	5,70	327057*
	Ø 45	+0,3/+1,3	3000	7,11	327058*
	Ø 50	+0,3/+1,3	3000	8,76	327059*
	Ø 56	+0,3/+1,3	3000	10,95	108805
	Ø 60	+0,3/+1,6	3000	12,60	327060*
	Ø 65	+0,3/+1,6	3000	14,76	108812
	Ø 70	+0,3/+1,6	3000	17,07	108994
	Ø 75	+0,4/+2,0	3000	19,71	108814
	Ø 80	+0,4/+2,0	3000	22,38	327047*
	Ø 90	+0,5/+2,2	3000	28,29	108828
	Ø 100	+0,6/+2,5	3000	34,95	327048*
	Ø 110	+0,7/+3,0	1000	14,15	363444
	Ø 110	+0,7/+3,0	3000	42,45	327049*
	Ø 120	+0,8/+3,5	1000	16,90	112793
	Ø 120	+0,8/+3,5	3000	50,70	109174
	Ø 125	+0,8/+3,5	1000	18,30	108847
	Ø 130	+0,9/+3,8	1000	19,80	108850
	Ø 140	+0,9/+3,8	1000	22,90	108851
	Ø 150	+1,0/+4,2	1000	26,35	112021
	Ø 160	+1,1/+4,5	1000	30,00	112020
	Ø 180	+1,2/+5,0	1000	37,90	112440
	Ø 200	+1,3/+5,5	1000	46,80	114064
	Ø 250	+1,5/+6,2	1000	72,85	112783
	Ø 300	+1,7/+7,0	1000	104,70	128783
	Ø 320	+1,8/+7,4	1000	119,00	159141

\*) LGM - Livsmedelsgodkänt Material